



**Bremstrommeln für MAN Lkw**

sonstige Bohrungen: 3x M 12x1,5

ø innen (mm)	Breite Belaglauf- fläche (mm)	Höhe (mm)	Nabensitz (mm)	ø Lochkreis (mm)	Anzahl Rad- bolzenbohrungen	ø Radbolzen- bohrung (mm)	Bestell-Nr.
325	107	167	204	245	6	20	311 720 045 00
325	157	192	204	245	6	19,7	311 720 043 00
360	148	200	230	275	8	22	311 720 048 00
360	168	245	230	275	8	22	311 720 046 00
360	185	247	230	275	8	22	311 720 058 00
410	167	213	298	335	10	23	311 720 036 00
410	167	250	298	335	10	23	311 720 047 00
410	187	232	298	335	10	23	311 720 042 00
410	192	280	298	335	10	23	311 720 033 00
410	235	300	298	335	10	23	311 720 028 00



**Bremstrommeln für Mercedes Lkw**

ø innen (mm)	Breite Belaglauf- fläche (mm)	Höhe (mm)	Nabensitz (mm)	ø Lochkreis (mm)	Anzahl Rad- bolzenbohrungen	ø Radbolzen- bohrung (mm)	sonstige Bohrungen	Bestell-Nr.
308	132	292		205	6	18		311 301 163 00
364	142	193	238	275	8	21	3x M 12x1,5	311 301 172 00
364	172	209	238	275	8	21	3x M 12x1,5	311 301 171 00
410	167	213	298	335	10	23	3x M 12x1,5	311 301 100 00
410	191	237	298	335	10	23	3x M 12x1,5	311 301 180 00
410	192	280	298	335	10	23	3x M 12x1,5	311 301 126 00
410	195	260	297	332	15	23	3x M 12x1,5	311 301 174 00
410	236	306	298	335	10	23	3x M 12x1,5	311 301 137 00
410	241	306	298	335	10	23		311 301 020 00