



## Krähenfuss-Leitungsschlüssel

Profil: Zwölfkant  
 Material: Spezialstahl  
 Oberfläche: brüniert

Antrieb (Zoll)	Schlüsselweite (mm)	Bestell-Nr.
3/8	19	980 005 985 00
3/8	21	980 005 986 00
3/8	22	980 005 987 00
3/8	24	980 005 988 00
3/8	27	980 005 989 00
1/2	30	980 005 990 00
1/2	32	980 005 991 00
1/2	36	980 005 992 00
1/2	41	980 005 993 00
1/2	46	980 005 994 00



## Einsteck-Maulschlüssel

Profil: Sechskant  
 Material: Chrom-Vanadium-Stahl  
 Oberfläche: verchromt

Antrieb (mm)	Schlüsselweite (mm)	Länge (mm)	Breite Maul (mm)	Höhe Maul (mm)	Bestell-Nr.
9x12	7	36,5	20	5,5	980 008 653 00
9x12	8	37	21,5	5,5	980 008 654 00
9x12	9	37,5	23	5,5	980 008 655 00
9x12	10	38	24,5	5,5	980 008 643 00
9x12	11	38,5	26	5,5	980 008 644 00
9x12	12	38,5	27,5	5,5	980 008 645 00
9x12	13	39	29	5,5	980 008 646 00
9x12	14	42	31	7,5	980 008 647 00
9x12	15	42,5	33	7,5	980 008 648 00
9x12	16	43	35	7,5	980 008 649 00
9x12	17	43,5	37	7,5	980 008 650 00
9x12	18	44	39	7,5	980 008 651 00
9x12	19	45	41	7,5	980 008 652 00
14x18	13	56,5	30	7	980 008 656 00
14x18	14	57	32	7	980 008 657 00
14x18	15	57,5	34	7	980 008 658 00
14x18	16	58	35,5	9	980 008 659 00
14x18	17	58,5	37	9	980 008 660 00
14x18	18	59	39	9	980 008 661 00
14x18	19	59,5	41	9	980 008 662 00
14x18	21	60,5	45	11	980 008 663 00
14x18	22	61	47	11	980 008 664 00
14x18	24	62	51	11	980 008 665 00
14x18	27	68,5	58,5	13	980 008 666 00
14x18	30	70	63	13	980 008 667 00
14x18	32	71,5	65	13	980 008 668 00