



### Einsteck-Ringschlüssel, offen

Antrieb (mm): 9x12  
 Profil: Zwölfkant  
 Stiftsicherung: ja  
 Material: Chrom-Vanadium-Stahl  
 Oberfläche: verchromt

Schlüssel- weite (mm)	Länge (mm)	Breite Kopf (mm)	Höhe Kopf (mm)	Bestell-Nr.
10	21	21	11,0	980 013 879 00
11	22,5	22,5	11,0	980 013 880 00
12	23,7	23,7	11,0	980 013 881 00
13	25,2	25,2	11,0	980 013 882 00
14	27	27	12,0	980 013 883 00
17	31,5	31,5	12,0	980 013 884 00
18	33	33	14,5	980 013 885 00
19	34,5	34,5	14,5	980 013 886 00
22	39	39	14,5	980 013 887 00



### Einsteck-Ringschlüssel, offen

Antrieb (mm): 9x12  
 Profil: Doppelsechskant  
 Material: Chrom-Vanadium-Stahl  
 Oberfläche: verchromt

Schlüssel- weite (mm)	Länge (mm)	max. Anzugs- drehmoment (Nm)	Breite Kopf (mm)	Höhe Kopf (mm)	Bestell-Nr.
10	42,3	25	22	14,5	980 005 931 00
11	42,8	33	22,5	14,5	980 005 932 00
12	43,4	42	24	14,5	980 005 933 00
13	43,7	52	25	14,5	980 005 934 00
14	44,4	64	27	14,5	980 005 935 00
16	45,4	93	30	14,5	980 005 936 00
17	45,9	110	31,5	14,5	980 005 937 00
18	46,1	130	33	15	980 005 938 00
19	46,8	150	34,5	15	980 005 939 00
21	48	198	37,5	15	980 005 940 00
22	48,8	225	39	15	980 005 941 00

### Info

Über 1.000 weitere Werkzeuge finden Sie im winkler Spezialkatalog "Werkstatt- und Betriebsbedarf".

