



Einschraubstutzen gerade, UNF

Abdichtung Einschraubung: Dichtung
 Material: Stahl
 Oberfläche: Cr6 frei verzinkt

für ϕ Rohr A (mm)	Gewinde außen A (Zoll)	Gewinde außen B (Zoll)	Schlüsselweite Körper ES (mm)	Betriebsdruck (bar)	Bestell-Nr.
6	9/16-18 UNF	7/16-20 UNF	17	345	623 003 218 00
6	9/16-18 UNF	1/2-20 UNF	17	345	623 003 219 00
6	9/16-18 UNF	9/16-18 UNF	17	345	623 003 220 00
6	9/16-18 UNF	3/4-16 UNF	22	310	623 003 221 00
8, 10	11/16-16 UNF	7/16-20 UNF	19	345	623 003 222 00
8, 10	11/16-16 UNF	1/2-20 UNF	19	345	623 003 223 00
8, 10	11/16-16 UNF	9/16-18 UNF	19	345	623 003 224 00
8, 10	11/16-16 UNF	3/4-16 UNF	22	310	623 003 225 00
12	13/16-16 UNF	9/16-18 UNF	22	345	623 003 226 00
12	13/16-16 UNF	3/4-16 UNF	22	310	623 003 227 00
12	13/16-16 UNF	7/8-14 UNF	27	240	623 003 228 00
14, 15, 16	1-14 UNF	3/4-16 UNF	27	310	623 003 229 00
14, 15, 16	1-14 UNF	7/8-14 UNF	27	240	623 003 230 00
14, 15, 16	1-14 UNF	1 1/16-12 UNF	32	240	623 003 231 00
18, 20	1 3/16-12 UNF	7/8-14 UNF	32	240	623 003 232 00
18, 20	1 3/16-12 UNF	1 1/16 UNF	32	240	623 003 233 00
18, 20	1 3/16-12 UNF	1 5/16-12 UNF	38	210	623 003 234 00
22, 25	1 7/16-12 UNF	1 1/16-12 UNF	38	240	623 003 235 00
22, 25	1 7/16-12 UNF	1 5/16-12 UNF	38	210	623 003 236 00
22, 25	1 7/16-12 UNF	1 5/8-12 UNF	48	170	623 003 237 00
28, 30, 32	1 11/16-12 UNF	1 5/16-12 UNF	46	210	623 003 238 00
28, 30, 32	1 11/16-12 UNF	1 5/8-12 UNF	48	170	623 003 239 00
28, 30, 32	1 11/16-12 UNF	1 7/8-12 UNF	46	140	623 003 240 00
35, 38	2-12 UNF	1 7/8-12 UNF	55	140	623 003 241 00



Einschraubstutzen 45°, einstellbar, BSP

Winkel (°): 45
 Abdichtung A: flachdichtend mit O-Ring
 Abdichtung B: flachdichtend (Dichtung)
 Material: Stahl
 Oberfläche: Cr6 frei verzinkt

Gewinde außen A (Zoll)	Gewinde außen B (Zoll)	Betriebsdruck (bar)	Bestell-Nr.
9/16-18	1/8	420	623 003 382 00
9/16-18	1/4	420	623 003 383 00
11/16-16	1/4	420	623 003 384 00
11/16-16	3/8	420	623 003 385 00
11/16-16	1/2	300	623 003 386 00
13/16-16	3/8	420	623 003 387 00
1-14	1/2	300	623 003 388 00
1-14	3/4	175	623 003 389 00
1 3/16-12	3/4	175	623 003 390 00
1 3/16-12	1	150	623 003 391 00
1 7/16-12	1	150	623 003 392 00
1 11/16-12	1 1/4	150	623 003 393 00
2-12	1 1/4	150	623 003 394 00