



### Einschraubstutzen L-Form, UNF

Abdichtung Leitungsteil: flachdichtend mit O-Ring  
 Material: Stahl  
 Oberfläche: Cr6 frei verzinkt  
 Norm: SAE J 1453

für ø Rohr A, B (mm)	Gewinde außen A, B (Zoll)	Gewinde außen C (Zoll)	Bestell-Nr.
6	9/16-18 UNF	7/16-20 UNF	623 003 549 00
8, 10	11/16-16 UNF	9/16-18 UNF	623 003 550 00
12	13/16-16 UNF	3/4-16 UNF	623 003 551 00
14, 15, 16	1-14 UNF	7/8-14 UNF	623 003 552 00
18, 20	1 3/16-12 UNF	1 1/16-12 UNF	623 003 553 00
22, 25	1 7/16-12 UNF	1 5/16-12 UNF	623 003 554 00
30, 32	1 11/16-12 UNF	1 5/8-12 UNF	623 003 555 00



### Aufschraubadapter gerade, ORFS

Material: Stahl  
 Oberfläche: Cr6 frei verzinkt

Gewinde außen A (Zoll)	Gewinde innen B (Zoll)	Schlüsselweite Körper ES (mm)	Betriebsdruck (bar)	Bestell-Nr.
9/16-18 UNF	11/16-16 UNF	17	420	623 003 570 00
9/16-18 UNF	13/16-16 UNF	19	420	623 003 571 00
9/16-18 UNF	1-14 UNF	27	420	623 003 572 00
9/16-18 UNF	1 3/16-12 UNF	32	420	623 003 573 00
11/16-16 UNF	13/16-16 UNF	19	420	623 003 574 00
11/16-16 UNF	1-14 UNF	27	420	623 003 575 00
11/16-16 UNF	1 3/16-12 UNF	32	420	623 003 576 00
13/16-16 UNF	1-14 UNF	27	420	623 003 577 00
13/16-16 UNF	1 3/16-12 UNF	32	420	623 003 578 00
13/16-16 UNF	1 7/16-12 UNF	36	420	623 003 579 00
1-14 UNF	1 3/16-12 UNF	27	420	623 003 580 00
1-14 UNF	1 7/16-12 UNF	36	420	623 003 581 00
1 3/16-12 UNF	1 7/16-12 UNF	36	420	623 003 582 00
1 3/16-12 UNF	1 11/16-12 UNF	41	280	623 003 583 00
1 7/16-12 UNF	1 11/16-12 UNF	41	280	623 003 584 00