

Metrisch

**O-Ringe, metrisch**

Beständigkeit: Glykol, Hydrauliköl, Wasser, Öl

Material: NBR (Perbunan)

Materialhärte (Shore A): 70°

Temperaturbereich von (°C): -30

Temperaturbereich bis (°C): 100

Farbe: schwarz

Norm (DIN): 3771

Norm (DIN ISO): 3601/1

ø innen (mm)	ø außen (mm)	Dicke (mm)	Bestell-Nr.
3	7	2	623 001 130 00
4	8	2	623 001 131 00
5	9	2	623 001 132 00
6	10	2	623 001 133 00
7	11	2	623 001 134 00
8	12	2	623 001 135 00
10	14	2	623 001 136 00
10	15	2,5	623 001 137 00
11	16	2,5	623 001 138 00
12	17	2,5	623 001 139 00
14	19	2,5	623 001 140 00
16	21	2,5	623 001 141 00
17	22	2,5	623 001 142 00
19	24	2,5	623 001 143 00
19	25	3	623 001 144 00
20	26	3	623 001 145 00
22	28	3	623 001 146 00
24	30	3	623 001 147 00
25	31	3	623 001 148 00
27	33	3	623 001 149 00
28	34	3	623 001 150 00
30	36	3	623 001 151 00
32	38	3	623 001 152 00
33	39	3	623 001 153 00
35	41	3	623 001 154 00
36	42	3	623 001 155 00
38	44	3	623 001 156 00
38	46	4	623 001 157 00
42	50	4	623 001 158 00
45	53	4	623 001 159 00